



KEACO INC.
6410 TRI COUNTY PARKWAY
SCHERTZ, TX 78154

TEL: (210) 651-6688
FAX: (210) 651-9020

TECHNICAL DATA SHEET

7" LIGHT WEIGHT SMD REELS

Keaco light weight SMD reels feature a one-piece polystyrene construction with no assembly required. All light weight SMD reels meet current EIA-481 standards. This product is recommended when a good quality 7" SMD reel is needed at the lowest possible cost.

Typical Electrical Properties for 7" Light Weight SMD Reels

Surface Resistivity (ASTM D-257 at 50% RH): $\leq 10^{11}$ ohms / square
Static Decay (EIA -541 Method 4046 of Standard 101C at 50% RH): 90% discharge in .14 sec.;
100% discharge in 1.48 sec.

<u>Reel Sizes</u>	<u>Hub Diameter / Type</u>	<u>Reels / Box</u>	<u>Weight / Box (lbs)</u>	<u>Qty. / Pallet</u>
7" x 8mm	60mm / Round	150	16	3,750
7" x 12mm	60mm / Round	114	14	2,850

8/3/2005

The information above is based on our experience to date and we believe it to be reliable. It is intended only as a guide for use at your discretion and risk. We assume no liability in connection with the use of the product described above. None of the information herein shall be taken as a license to operate under, or a recommendation to infringe, any patents. KEACO INC. makes no warranty, expressed or implied, as to the suitability of these materials for any specific use.