



KEACO INC.  
6410 TRI COUNTY PARKWAY  
SCHERTZ, TX 78154

TEL: (210) 651-6688  
FAX: (210) 651-9020

# TECHNICAL DATA SHEET

## CCD/KEACO™ SMD REELS

CCD/KEACO™ SMD Reels feature a sturdy one-piece polystyrene construction with no assembly required. All CCD/KEACO™ SMD reels meet current EIA-481 standards.

### Typical Electrical Properties for Internally Antistatic SMD Reels

Surface Resistivity (ASTM D-257 at 50% RH):  $\leq 10^{11}$  ohms / square  
 Static Decay (EIA -541 Method 4046 of Standard 101C at 50% RH): 90% discharge in .14 sec.;  
 100% discharge in 1.48 sec.

### Typical Electrical Properties for Externally Antistatic SMD Reels

Surface Resistivity (ASTM D-257 at 12% RH):  $\leq 10^9$  ohms / square  
 Static Decay (EIA-541 Method 4046 of standard 101C at 12% RH): 100% discharge in .05 sec.

Reel Sizes	Hub Diameter / Type	Reels / Box	Weight / Box (lbs)	Qty. / Pallet
7" x 8mm	60mm / Round	144	19	3,600
7" x 12mm	60mm / Round	108	17	2,700
11.25" x 8mm	60mm / Round	36	25	1,440
11.25" x 8mm	85mm / Round	36	25	1,440
11.25" x 8mm	100mm / Round	36	25	1,440
11.25" x 12mm	60mm / Round	29	21	1,160
11.25" x 12mm	100mm / Round	29	21	1,160
13" x 8mm	60mm / Round	52	33	1,560
13" x 8mm	100mm / Round	52	33	1,560
13" x 12mm	60mm / Round	40	24	1,200
13" x 12mm	100mm / Round	40	24	1,200
13" x 16mm	100mm / Scroll Start	32	21	960
13" x 24mm	100mm / Scroll Start	24	17	660
13" x 32mm	100mm / Scroll Start	18	13	540
13" x 44mm	150mm / Scroll Start	12	12	288

12/5/2006

The information above is based on our experience to date and we believe it to be reliable. It is intended only as a guide for use at your discretion and risk. We assume no liability in connection with the use of the product described above. None of the information herein shall be taken as a license to operate under, or a recommendation to infringe, any patents. KEACO INC. makes no warranty, expressed or implied, as to the suitability of these materials for any specific use.